

Flange plug connector

Pre-wired
0.2 m

Male M12



Female M12



1	Form	No.	13501	13521	13541	13561
	Suppression/Circuit diagram		4-pole	5-pole	4-pole	5-pole
	Contact layout					
2	Wire		971	972	971	972
	Suitable mounting nut M16 x1.5	Art.-No. 7000-13581-000 0000				
	Technical data					
	Supply voltage	250 V AC/DC		125 V AC/DC	250 V AC/DC	125 V AC/DC
	Current per contact (40 °C)	max. 4 A				
	Connection	soldering, wire (TPE-wire isolation) manufactured				
	Connection diameter	0.25 mm ²				
	Protection	IP67 when plugged and screwed down (EN 60529)				
	Temperature range	-25...+85 °C				
	Your article no.					
	The composition of your article number is explained on page 1.1.2	7000 - - 0020 Murrelektronik Standard				
		1		Form	2	Cable type
	Notes					

Flange plug connector



Pre-wired
0.2 m

Male M12



Female M12



1	Form	No.	17161	17181
	Suppression/Circuit diagram	8-pole	8-pole	8-pole
	Contact layout	Male	Female	
	Wire	973	973	
2	Suitable mounting nut M16 x1.5	Art.-No. 7000-13581-000 0000		
	Technical data			
	Supply voltage	60 V AC/DC		
	Current per contact (40 °C)	2 A		
	Connection	soldering, wire (TPE-wire isolation) manufactured		
	Connection diameter	0.25 mm ²		
	Protection	IP67 when plugged and screwed down (EN 60529)		
	Temperature range	-25...+85 °C		
	Your article no.			
	The composition of your article number is explained on page 1.1.2	7000 - - 0020 Murrelektronik Standard		
		1 Form2 Cable type		
	Notes			

Flange plug connector

Pre-wired
0.2 m

B-coded



Male M12



Female M12



1	Form	No.	1 4 1 2 1	1 4 1 6 1
	Suppression/Circuit diagram	5-pole	1 2 4 3 5 brown (+) white (N/C) black (N/O) blue (-) green/yellow (PE)	1 2 4 3 5 brown (+) white (N/C) black (N/O) blue (-) green/yellow (PE)
	Contact layout		Male 4 3 5 1 2	Female 3 4 5 2 1
2	Wire			
		975		975
	Suitable mounting nut M16 x1.5	Art.-No. 7000-13581-000 0000		
	Technical data			
	Supply voltage	250 V AC/DC	125 V AC/DC	250 V AC/DC
	Current per contact	max. 4 A		125 V AC/DC
	Connection	soldering, wire (TPE-wire isolation) manufactured		
	Connection diameter	0.25 mm ²		
	Protection	IP67 when plugged and screwed down (EN 60529)		
	Temperature range	-25...+85 °C		
	Your article no.			
	The composition of your article number is explained on page 1.1.2	7000 Murrelektronik Standard	— — — — —	975 0020
		1	Form	2
				Cable type
	Notes			

Flange plug connector

Control panel entry system

Male/Female M12







Cube67





1

Form	No.	42111	44111	46111	48111
------	-----	-------	-------	-------	-------

Suppression/Circuit diagram	5-pole	5-pole, B-coded	6-pole	8-pole
-----------------------------	--------	-----------------	--------	--------



Contact layout



Technical data

Supply voltage	24 V AC/DC	
Current per contact	4 A	1.5 A
Mounting thread	M16 x 1.5	
Protection	IP67 when plugged and screwed down (EN 60529)	
Temperature range	-25...+85 °C	

Your article no.

The composition of your article number is explained on page 1.1.2

7 0 0 0
Murrelektronik
Standard

-

— — — — —

-

0 0 0

0 0 0 0

1 Form

Notes